



Easy Pro View IP Camera's



Technische specificaties

	EM6270	EM6250HD	EM6250	EM6260
Dimensions in mm. (WxHxD)	88x126x100	65x100x35	65x100x35	55x54x140
Weight in grams	318	106	105	363
Power by external power supply:	DC 12V, 1A	DC 12V, 1A or DC 5V, 1A	DC 12V, 1A or DC 5V, 1A	DC 20V/0.6A
Network interface: Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45	✓	✓	✓	✓
Wireless interface: IEEE 802.11n 90 - 150 Mbps and WPS	✓	✓	✓	✓
Security: Web management username/password protection WiFi WEP and WPA/WPA2 security mode	✓	✓	✓	✓
Pan/Tilt: Pan viewing range 180° (-90° ~ 90°) Tilt viewing range 90° (0° ~ 90°)	✓	✗	✗	✗
Image sensor: RGB VGA 1/4 inch CMOS, Day and night separate sensors, Automatic exposure control, Automatic white balance, Automatic gain control, Automatic brightness control	✓	✓	✓	✓
Infrared thermometer: Range: -40 ~ 115 °C, accuracy:±0.5°C	✓	✓	✗	✗
PIR sensor: Effective distance – 7 meters	✓	✓	✓	✗
Field of view	66°	66°	60,3°	62°
Focus range: 30 cm to infinity	✓	✓	✓	✓
Day and night: separate lenses	✓	✓	✓	✓
HD sensors	✓	✓	✗	✓
Video compression: H.264, baseline profile level 3.1	✓	✓	✓	✓
Video streaming: Separate frame rate/resolution/bandwidth settings for PC and mobile	✓	✓	✓	✓
Video resolution: HD for PC: 1280x800, HD for Android & iOS 1024x768	✓	✓	✗	✓
Video resolution: VGA(640x480), QVGA(320x240), QQVGA(160x120)	✓	✓	✓	✓
Bandwidth: 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M, 2M	✓	✓	✗	✓
Bandwidth: 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M	✓	✓	✓	✓
Frame rate: 1~5, 10, 15, 20, 25, 30 fps	✓	✓	✓	✓
Audio: Built-in, Speaker jack for external speaker, Audio compression: G.711	✓	✓	✓	✗
Microphone for audio monitoring	✓	✓	✓	✓
Internal speaker	✓	✓	✗	✗
Web browsing: Built-in web server for standard web browser access Video display on IE browser, Video snapshot on any browser	✓	✓	✓	✓
Supported protocols: IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE	✓	✓	✓	✓
Video management software: Surveillance software for viewing and archiving up to 36 cameras	✓	✓	✓	✓
Users: Up to 20 simultaneous unicast users (depends on video settings)	✓	✓	✓	✓
Alarm and event management: Events triggered by PIR	✓	✓	✓	✗
Alarm and event management: Events triggered by temperature	✓	✓	✗	✗
Alarm and event management: Events triggered by motion and sound detection	✓	✓	✓	✓
Email/ftp alarm message, Push notification on iPhone/iPad and Android devices	✓	✓	✓	✓
Operating conditions	0 - 50°C	0 - 50°C	0 - 50°C	-30 - 50°C
Humidity: 20 – 80% RH (non-condensing)	✓	✓	✓	✓
For outdoor use	✗	✗	✗	✓
IP66 rate housing	✗	✗	✗	✓

5**jaar
garantie****Toegankelijke
helpdesk****Nederlandstalige
handleiding****Eenvoudige
installatie****WWW.EMINENT-ONLINE.COM**

UW DEALER